



HP Designjet T1500 ePrinter series

419.241.5157 www.newfaxcorp.com

Newly designed, two-roll, web-connected ePrinter for demanding teams



Innovative user experience

- Eliminate the output clutter—get flat, collated prints thanks to the integrated output stacking tray.
- Gain control—monitor media rolls, view printer status on the touchscreen, and track jobs during printing.
- Load two paper rolls effortlessly—even when seated—with front loading and automatic paper-roll alignment.
- Print up to AO/E with a compact, 36-inch printer designed with a flat surface for quick checking of your printouts.

Top performance in multi-user environments

- Help cut downtime—print multiple jobs on different media types and sizes with two rolls and smart switching.
- Manage job queues, track print costs, print borderless¹ images, get what you see with true print previews.
- Get dark blacks, true neutral grays, and vivid colors with six Original HP inks and the HP printhead.
- Print complex files fast—one A1/D-size in 21 seconds with a 320-GB hard drive and parallel processing power.

Print from virtually anywhere²

- Use your Apple[®] or Android[™] smartphone or tablet to print from virtually anywhere².
- Access and print projects when you're out of the office, using HP Designjet ePrint & Share² or USB printing.
- Automatically save copies of your projects to the cloud when you print using HP Designjet ePrint & Share².
- Print without drivers using a USB stick or directly email projects to your HP Designjet T1500 ePrinter².

For more information, please visit hp.com/go/DesignjetT1500

Photo paper is required to print borderless images.

² Requires an HP Designjet ePrint & Share account, Internet connection to the printer, and connected Internet-capable device. When using the HP Designjet ePrint & Share mobile app, a compatible Apple[®] iOS or Android[™] device and Internet connection are required. Data or connection charges may apply. Print times may vary. For more information, visit <u>hp.com/go/eprintandshare</u>.



- With Aurasma installed, please go to the HP Designjet channel at <u>http://auras.ma/s/ke25m</u>
 Without Aurasma installed, please download it:
 - a. Google Play <u>http://auras.ma/s/android</u>
 - b. Apple Store <u>http://auras.ma/s/ios</u>
 - Once done, go to the HP Designjet channel at http://auras.ma/s/ke25m
- 3. Open the application and point to the image to view the HP Designjet video

Technical specifications

Print resolution Up to 2400 x 1200 optimized dpi Margins (top x Roll: 5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 in) (borderless on bottom x left x photo papers) right) Sheet: 5 x 22 x 5 x 5 mm (0.2 x 0.87 x 0.2 x 0.2 in) Technology HP Thermal Inkjet Ink types Dye-based (C, G, M, pK, Y); pigment-based (mK) Ink drop 6 pl (C, M, Y, G, pK); pl (mK) Printheads 1 (C, G, M, mK, pK, Y) Line accuracy +/-0.1% ⁴ Minimum line width Guaranteed minimum line width Media Handling Input: two automatic front-loading roll feeds, smart roll switching, sheet feed; Output: integrated output stacking tray (from A/A) to 0.028 in) (ISO/IEC 13660:2001(E)) ⁵ minimum line width Media Handling Input: two automatic front-loading roll feeds, smart roll switching, sheet feed; Output: integrated output stacking tray (from A/A) to 0.012, with up to 50 A/10-size capacity), media bin, automatic cutter Weight 60 to 228 g/m ⁴ Size Dol 328 g/m ⁴ Size Dol 328 g/m ⁴ Size Optimer: 64 GB (virtual) ⁵ PostScript ePrinter: Adobe PostScript 3, Adobe PDE 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Print languages Basic ePrinter: Adobe PostScript 3, Adobe PDE 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printing paths Printer driver, HP Designjet ePrint 8, Share, HP Embedded Web Server, HP-Instant Printing, direct printing from USB flash drive, email printing Drivers HP-GL/2, HP-RTL, TifF, JPEG, CALS G4, HP PCL 3 GUI, URF Printer 1399 x 916 x 1110 mm (S5.1 x 36.1 x 43.7 in) Wieght Printer 1399 x 916 x 110 mm (S5.1 x 36.1 x 43.7 in) Weight Printer B8 kg (194 lb) Shipping 116.5 kg (256.3 ib) What's in the HP Designet temperature: 5 to 40°C (41 to 104'F) Targets Storage temperature: 5 to 40'C (41 to 104'F) Targets Storage temperature: 5 to 40°C (41 to 104'F) Targets Storage temperat				
Margins (top x Roll: 5 x 5 x 5 x 5 xm (0.2 x 0.2 x 0.2 ln) (borderless on photopapers) Technology HP ThermalInkjet Ink types Dye-based (C, G, M, PK, Y); pigment-based (mK) Ink drop 6 pl (C, M, Y, G, pK); 9 pl (mK) Printheads 1 (C, G, M, mK, pK, Y) Line accuracy +/- 0.1% ⁶ Minimum line 0.02 mm (0.0008 in) (HP-GL/2 addressable) width Guaranteed 0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E)) ⁵ Ine width Input: two automatic front-loading roll feeds, smart roll switching, sheet feed: 0.0170-size capacity), media bin, automatic cutter Weight 60 to 328 g/m² Size Size Rolls: 279 to 914 mm (11 to 36 in) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) Memory Basic ePrinter: 64 GB (virtual) ⁶ , 3 GUI, URF PostScript ePrinter: 64 GB (virtual) ⁶ Sold Bard disk Connectivity Interfaces Gigabit Ethernet (1000 Base-T) (standard) Frintlanguages Basic ePrinter: AdoB PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printing paths Printer driver, HP Destinglet ePrint 8, Share, HP Embedded Web Server, HP	Print	Line drawings ³	21 sec/page on A1/D, 120 A1/D prints per hour	
botiom kleft × photo papers) right) Sheet: 5 × 2 × 5 × 5 m (0.2 × 0.87 × 0.2 × 0.2 × 0.2 × 0.7 × 0.2 ×		Print resolution	Up to 2400 x 1200 optimized dpi	
Technology HP Thermal Inkjet Ink types Dye-based (C, G, M, DK, Y); pigment-based (mk/) Ink drop 6 pl (C, M, Y, G, pK; 9 pl (mk) Printheads 1 (C, G, M, MK, pK, Y) Line accuracy +/- 0.1% Minimum line 0.02 mm (0.0008 in) (HP-GL/2 addressable) width Guaranteed minimum 0.07 mm (0.028 in) (ISO/IEC 13660:2001(E)) ⁶ minimum Input: two automatic front-loading roll feeds, smart roll switching, sheet feed; Output: integrated output stacking tray, (from A4/h to A0/E, with up to 50 A1/D-size capacity), media bin, automatic cutter Weight 60 to 328 g/m² Size Rolls: 2710 914 mm (11 to 36 in) Sheets: 210 x 279 to 914 x, 11 to 36 x, 48 in) Standard Sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) PostScript ePrinter: 64 G8 (virtual) ^k , 320 G8 hard disk Connectivity' Interfaces Thickness Gigabit Ethernet (1000 Base-1) (standard) Solid, URF Print Languages Basic ePrinter: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printer g8 kg (1941 lb) <td></td> <td></td>				
Ink types Dye-based (C, G, M, pK, Y); pigment-based (mK) Ink drop 6 pl (C, M, Y, G, pK); Pp (mK) Printheads 1 (C, G, M, mK, pK, Y) Line accuracy +/- 0.1% Minimum line 0.02 mm (0.0008 in) (HP-GL/2 addressable) width Guaranteed 0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E))* Ine width Ine width Ine width Media Handling Input: two automatic front-loading roll feeds, smart roll switching, sheet feed: Output: Integrated output stacking tray (from A4/A to A0/E, with up to 50 A1/O-size capacity), media bin, automatic cutter Weight 60 to 328 g/m² Size Size Rolls: 279 to 914 mm (11 to 36 in) Standard sheets: AA, A3, A2, A1, A0 (A, B, C, D, E) Thickness Thickness Up to 0.5 mm (19.7 mil) Basic ePrinter: 64 GB (virtual) ^{is} PostScript ePrinter: 64 GB (virtual) ^{is} PostScript ePrinter: 64 GB (virtual) ^{is} Sold GB hard disk Connectivity? Interfaces Gigbli Ethernet (1000 Base-1) Standard Sold U, UPF PostScript ePrinter: ADe PostDe PostScript 3, Adobe POF 1.7 Extendent Printer driver, HP Designjet ePrintA Share, HP Embedded Web				
ink drop 6 pl (C, M, Y, G, pk); 9 pl (mk) Printheads 1 (C, G, M, mk, pk, Y) Line accuracy +/- 0.1% ⁴ Minimum line 0.02 mm (0.0028 in) (ISO/IEC 13660:2001(E)) ⁵ Guaranted 0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E)) ⁵ Inine width Input: two automatic front-loading roll feeds, smart roll switching, sheet feed; Output: Integrated output stacking tray from A/A to A/D, with up to 50 AI/D-size capacity), media bin, automatic cutter Weight 60 to 328 g/m ² Size Rolls: 279 to 914 xn 219 mm (8.3 x 11 to 36 x 48 in) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) Memory Basic ePrinter: 64 GB (virtual) ⁵ PostScript ePrinter: 66 GB (virtual) ⁵ PostScript ePrinter: 64 GB (virtual) ⁵ PostScript eQ (virtual) ⁶ PostScript ePrinter: 64 GB (virtual) ⁷ Otint targases Basic ePrinter: HP-GL/2, HP-RTL, T		Technology	HP Thermal Inkjet	
Printheads 1 (C, G, M, mK, pK, Y) Line accuracy +/- 0.1% ⁶ Minimum line 0.02 mm (0.0008 in) (HP-GL/2 addressable) width 0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E)) ⁶ Minimum Input: two automatic front-loading roll feeds, smart roll switching, sheet feed; Output: integrated output stacking tray from A/A to A/JC, with up to SOAI/D-size capacity), media bin, automatic cutter Weight 60 to 328 g/m ² Size Rolls: 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) Memory Basic ePrinter: 64 GB (virtual) ⁹ PostScript ePrinter: ADe CL2, HP-RTL TIFF, JPEG, CALS G4, HP PCL (standard) 3 GU, UFF Printing paths Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Drivers Printer 1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) Weight Printer 88 kg (194 lb)		Ink types	Dye-based (C, G, M, pK, Y); pigment-based (mK)	
Line accuracy +/- 0.1% ⁴ Minimum line 0.02 mm (0.0008 in) (HP-GL/2 addressable) width 0.07 mm (0.0028 in) (ISO/IEC 13660-2001(E)) ⁵ Inne width Input: two automatic front-loading roll feeds, smart roll switching, sheet feed; Output: integrade output stacking tray (from A4/A to A0/E, with up to 50 A1/D-size capacity), media bin, automatic cutter Weight 60 to 328 g/m ² Size Rolls: 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Sheets: 300 up to 0.5 mm (19.7 mil) Memory Basic ePrinter: 64 GB (virtual) ⁵ postScript Perinter: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printer gapats Printer driver, HP Desingiet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Drivers HP-GL/2, HP-RTL drivers for Windows, Inux, and Mac drivers ⁶ Dimensions Shipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Wat's in the box Shipping 116.5 kg (256.3 lb) What		Ink drop	6 pl (C, M, Y, G, pK); 9 pl (mK)	
Minimum line width 0.02 mm (0.0008 in) (HP-GL/2 addressable) width Guaranteed minimum line width 0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E))* Media Handling Input: two automatic front-loading roll feeds, smart roll switching, sheet feed; Output: integrated output stacking tray from A4/A to AO/E, with up to 50 A1/D-size capacity), media bin, automatic cutter Weight 60 to 328 g/m² Size Rolls: Z79 to 914 mm (11 to 36 in) Sheets: 210 x Z79 to 914 x 121 mm (8.3 x 11 to 36 x 48 in) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) Memory Basic ePrinter: 64 GB (virtual)* PostScript ePrinter: 44 DP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL (standard) Printlanguages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printing paths Printer, 149 Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Drivers HP-GL/2, HP-RTL drivers for Windows, Linux, and Mac drivers ⁶ Dimensions Printer 1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) Shipping 1102 X 759 x 775 mm (59.1 x 29.9 x 30.5 in) Mac 51 x 140 Weight Printer 88 kg (1941 lb)		Printheads	1 (C, G, M, mK, pK, Y)	
width Guaranteed minimum line width Media Handling Input: two automatic front-loading roll feeds, smart roll switching, sheet feed; Output: integrated output stacking tray (from A4/A to A0/E, with up to 50 A1/D-size capacity), media bin, automatic cutter Weight 60 to 328 g/m² Size Rolls: 270 to 914 wn (11 to 36 in) Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) Basic ePrinter: 64 GB (virtual) ⁶ , 220 GB hard disk Connectivity Interfaces (standard) Siguit Ethernet (1000 Base-T) Standard Siguit UFF PostScript ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL (standard) Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL (standard) Dimensions Printer driver, HP Designjet ePrint & Share, HP embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Dimensions Printer 1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) Mx 4 x h) Shipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Weight Printer 1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) Mx 4 x h) Shipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in)		Line accuracy	+/- 0.1%4	
minimum line width Media Handling Input: two automatic front-loading roll feeds, smart roll switching, sheet feed; Output: integrated output stacking tray (from A4/A to A0/E, withup to 50 A1/D-size capacity), media bin, automatic cutter Weight 60 to 328 g/m² Size Rolls: 279 to 914 xm (11 to 36 in) Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) Memory Basic ePrinter: 64 GB (virtual) ⁶ PostScript ePrinter: 64 GB (virtual) ⁶ Standard) Print languages Basic ePrinter: Adobe DostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL (standard) Trivers Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Drivers PH-GL/2, HP-RTL drivers for Windows ⁶ ; HP PCL 3 GUI driver for (included MP-GL/2, HP-RTL drivers for Windows ⁶ ; HP PCL 3 GUI driver for (included Dimensions Printer 1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) Weight Printer 1399 x 916 x 1110 mm (55.1 x 29.9 x 30.5 in) Weight Printer 88 kg (194 lb) Shipping 1150 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Weight Proescipt and thereference guide, setup poster, st			0.02 mm (0.0008 in) (HP-GL/2 addressable)	
 Switching, sheet feed; Output: integrated output stacking tray (from A4/A to A0/E, with up to 50 A1/D-size capacity), media bin, automatic cutter Weight 60 to 328 g/m² Size Rolls: 279 to 914 xm (11 to 36 in) Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Sheats: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Sheats: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Sheats: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Sheats: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Sheats: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Sheats: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Sheats: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Sheats: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Sheats: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Sheats: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Sheats: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Sheat (100 Base-T) (100 Ba		minimum	0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E)) ⁵	
Size Rolls: 279 to 914 mm (11 to 36 in) Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) Memory Basic ePrinter: 64 GB (virtual) ⁶ PostScript ePrinter: 64 GB (virtual) ⁶ , 320 GB hard disk Connectivity? Interfaces Gigabit Ethernet (1000 Base-T) (standard) Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL (standard) Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL (standard) Printing paths Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Drivers HP-GL/2, HP-RTL drivers for Windows [®] ; HP PCL 3 GUI driver for (included) Mac OS X; PostScript Windows, Linux, and Mac drivers [®] Dimensions Printer Printer 1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) Weight Printer Shipping 116.2 kg (256.3 lb) What's in the box Ph Designjet T1500 ePrinter, printhead, ink cartridges, stacking tray, printer stan and media bin, spindles, quick reference guide, setup poster, startup software, power cord Cacoustic Sound pressure: 47 dB(A) (printing); 5.8 B(A) (ready); <15 dB(A) (sleep)	Media	Handling	switching, sheet feed; Output: integrated output stacking tray (from A4/A to A0/E, with up to 50 A1/D-size capacity), media	
Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) Basic ePrinter: 64 GB (virtual) ⁶ PostScript ePrinter: 64 GB (virtual) ⁶ , 320 GB hard disk Connectivity' Interfaces Gigabit Ethernet (1000 Base-T) (standard) Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL (standard) PPCL 3 GUI, URF Printing paths Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Drivers HP-GL/2, HP-RTL drivers for Windows [®] ; HP PCL 3 GUI driver for (included) Mac 05 X; PostScript Windows, Linux, and Mac drivers [®] Dimensions Printer 1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) Weight Printer 88 (g (194 lb) Shipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Weat's in the box HP Designjett T1500 ePrinter, printhead, ink cartridges, stacking tray, printer stan- and media bin, spindles, quick reference guide, setup poster, startup software, power cord Environmental Operating temperature: 5 to 40°C (41 to 104°F) Tanges Storage temperature: 5 to 40°C (41 to 104°F) Sound power: 6.5 B(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep) Sou		Weight	60 to 328 g/m ²	
Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) Memory Basic ePrinter: 64 GB (virtual) ⁶ , 320 GB hard disk PostScript ePrinter: 64 GB (virtual) ⁶ , 320 GB hard disk Connectivity' Interfaces (standard) Gigabit Ethernet (1000 Base-T) (standard) Print languages Basic ePrinter: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printing paths Printer driver, HP Designjet ePrinte Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Dimensions Printer 1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) Wx d x h) Shipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Weight Printer 88 kg (194 lb) Shipping 115.5 kg (256.3 lb) PH What's in the box PD perating temperature: 5 to 40°C (41 to 104°F) Storage temperature: 5 to 40°C (41 to 104°F) St		Size	Rolls: 279 to 914 mm (11 to 36 in)	
Thickness Up to 0.5 mm (19.7 mil) Memory Basic ePrinter: 64 GB (virtual) ⁶ , 320 GB hard disk Connectivity? Interfaces Gigabit Ethernet (1000 Base-T) (standard) Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL (standard) Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF PostScript® ePrinter: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printing paths Printer driver, HP Designiet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Driver HP-GL/2, HP-RTL drivers for Windows®; HP PCL 3 GUI driver for (included) Mac OS X; PostScript Windows, Linux, and Mac drivers® Dimensions Printer 1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) (w x d xh) Shipping 150.2 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Weight Printer 88 kg (194 lb) Shipping 116.5 kg (256.3 lb) What's in the box HP Designiet T1500 ePrinter, printhead, ink cartridges, stacking tray, printer stan and media bin, spindles, quick reference guide, setup poster, startup software, power cord Carviornemtal Operating temperature: > 5 to 40°C (41 to 104°F)				
Memory Basic ePrinter: 64 GB (virtual) ⁶ , 320 GB hard disk Connectivity ⁷ Interfaces Gigabit Ethernet (1000 Base-T) (standard) Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL (standard) Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL (standard) Print languages Basic eVerinter: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printing paths Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Drivers HP-GL/2, HP-RTL drivers for Windows [®] ; HP PCL 3 GUI driver for (included) Mac OS X; PostScript Windows, Linux, and Mac drivers [®] Dimensions Printer Vat x h) Shipping Shipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Weight Printer Bask g (194 lb) Shipping 116.5 kg (256.3 lb) What's in the box PD perating temperature: 5 to 40°C (41 to 104°F) ranges Storage temperature: 25 to 55°C (-13 to 131°F) Operating humidity: 20 to 809 RH Acoustic Acoustic Sound power: 6.5 B(A) (printing); 39 dB(A) (ready); <16				
PostScript ePrinter: 64 GB (virtual) ⁶ , 320 GB hard disk Connectivity' Interfaces (standard) Gigabit Ethernet (1000 Base-T) (standard) Print languages (standard) Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF PostScript® ePrinter: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printing paths Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Dimensions Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Dimensions Printer 1399 x 916 x 1110 mm (55.1 x 43.7 in) Wix x x h) Shipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Weight Printer 88 kg (194 lb) Shipping 116.5 kg (256.3 lb) What's in the box HP Designjet T1500 ePrinter, printhead, ink cartridges, stacking tray, printer stan- and media bin, spindles, quick reference guide, setup poster, startup software, power cord Environmental Operating temperature: -5 to 40°C (41 to 104°F) Storage temperature: -2 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound power: 6.5 B(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)				
Connectivity' Interfaces (standard) Gigabit Ethernet (1000 Base-T) (standard) Print languages (standard) Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL (standard) PCL 3 GUI, URF PostScript® ePrinter: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printing paths Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Drivers HP-GL/2, HP-RTL drivers for Windows®; HP PCL 3 GUI driver for (included) Mac OS X; PostScript Windows, Linux, and Mac drivers® Dimensions Printer Mac OS X; PostScript Windows, Linux, and Mac drivers® Dimensions Printer Mat's in the Printer Printer 88 kg (194 lb) Shipping 116.5 kg (256.3 lb) What's in the HP Designjet T1500 ePrinter, printhead, ink cartridges, stacking tray, printer stan- and media bin, spindles, quick reference guide, setup poster, startup software, power cord Environmental consumption Operating temperature: 5 to 40°C (41 to 104°F) Storage temperature: 25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound power: 6.5 B(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)	Memory			
(standard) 3 GU, URF PostScript® ePrinter: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printing paths Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Dimensions Printer Printer 1399 x916 x1110 mm (55.1 x 36.1 x 43.7 in) Shipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Weight Printer Printer 88 kg (194 lb) Shipping 116.5 kg (256.3 lb) What's in the box HP Designjet T1500 ePrinter, printhead, ink cartridges, stacking tray, printer stanand media bin, spindles, quick reference guide, setup poster, startup software, power cord Environmental Operating temperature: 25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)	Connectivity ⁷	Interfaces		
HP PCL 3 GUI, URF Printing paths Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive. email printing Drivers HP-GL/2, HP-RTL drivers for Windows®; HP PCL 3 GUI driver for (included) Mac 0S X; PostScript Windows, Linux, and Mac drivers® Dimensions (w x d x h) Printer Shipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Weight Printer Printer 88 kg (194 lb) Shipping 116.5 kg (256.3 lb) What's in the box HP Designjet T1500 ePrinter, printhead, ink cartridges, stacking tray, printer stan and media bin, spindles, quick reference guide, setup poster, startup software, power cord Environmental Operating temperature: 5 to 40°C (41 to 104°F) Storage temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)			3 GUI, URF PostScript® ePrinter: Adobe PostScript 3, Adobe PDF 1.7	
Server, HP Instant Printing, direct printing from USB flash drive, email printing Drivers HP-GL/2, HP-RTL drivers for Windows®; HP PCL 3 GUI driver for (included) Mac OS X; PostScript Windows, Linux, and Mac drivers® Dimensions (w x d x h) Printer 1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) Weight Printer 88 kg (194 lb) Shipping 116.5 kg (256.3 lb) What's in the box HP Designjet T1500 ePrinter, printhead, ink cartridges, stacking tray, printer stan- and media bin, spindles, quick reference guide, setup poster, startup software, power cord Environmental ranges Operating temperature: 5 to 40°C (41 to 104°F) Storage temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)				
(included) Mac OS X; PostScript Windows, Linux, and Mac drivers® Dimensions (wx d x h) Printer 1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) Shipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Weight Printer 88 kg (194 lb) Shipping 116.5 kg (256.3 lb) What's in the box HP Designjet T1500 ePrinter, printhead, ink cartridges, stacking tray, printer stan- and media bin, spindles, quick reference guide, setup poster, startup software, power cord Environmental ranges Operating temperature: 5 to 40°C (41 to 104°F) Storage temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)		Printing paths	Server, HP Instant Printing, direct printing from USB flash drive,	
(w x d x h) Shipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Weight Printer 88 kg (194 lb) Shipping 116.5 kg (256.3 lb) What's in the box HP Designjet T1500 ePrinter, printhead, ink cartridges, stacking tray, printer stand and media bin, spindles, quick reference guide, setup poster, startup software, power cord Environmental Operating temperature: 5 to 40°C (41 to 104°F) Storage temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)			HP-GL/2, HP-RTL drivers for Windows®; HP PCL 3 GUI driver for Mac OS X; PostScript Windows, Linux, and Mac drivers ⁸	
Weight Printer 88 kg (194 lb) Shipping 116.5 kg (256.3 lb) What's in the box HP Designjet T1500 ePrinter, printhead, ink cartridges, stacking tray, printer stan- and media bin, spindles, quick reference guide, setup poster, startup software, power cord Environmental Operating temperature: 5 to 40°C (41 to 104°F) Grange temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)		Printer	1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in)	
Shipping 116.5 kg (256.3 lb) What's in the box HP Designjet T1500 ePrinter, printhead, ink cartridges, stacking tray, printer stan- and media bin, spindles, quick reference guide, setup poster, startup software, power cord Environmental Operating temperature: 5 to 40°C (41 to 104°F) ranges Storage temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 5.8 B(A) (ready); <16 dB(A) (sleep)	(w x d x h)	Shipping	1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in)	
What's in the box HP Designjet T1500 ePrinter, printhead, ink cartridges, stacking tray, printer stan- and media bin, spindles, quick reference guide, setup poster, startup software, power cord Environmental Operating temperature: 5 to 40°C (41 to 104°F) Storage temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep) Sound power: 6.5 B(A) (printing); 5.8 B(A) (ready); <1.9 B(A) (sleep) Power consumption Signal Front End) (sleep), 0.1 watts (auto-off), 0 watts (c7 watts with embedded Digital Front End) (sleep), 0.1 watts (auto-off), 0 watts (off hardswitch) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 4.2 A max (peak current) Certification Safety USA and Canada (CSA certified), EU (LVD and EN60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICS), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENEGY STAR, WEEE, EU RoHS, China RoHS, REACH, EuP, FEMP, EPEAT Bronze	Weight	Printer	88 kg (194 lb)	
box and media bin, spindles, quick reference guide, setup poster, startup software, power cord Environmental Operating temperature: 5 to 40°C (41 to 104°F) Storage temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)		Shipping	116.5 kg (256.3 lb)	
storage temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep) Sound power: 6.5 B(A) (printing); 5.8 B(A) (ready); <1.9 B(A) (sleep)		and media bin, spindles, quick reference guide, setup poster, startup software,		
Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep) Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep) Sound power: 6.5 B(A) (printing); 5.8 B(A) (ready); <1.9 B(A) (sleep) Power <120 watts (printing), <260 watts (maximum), <4 watts (<7 watts with embedded Digital Front End) (sleep), 0.1 watts (auto-off), 0 watts (off hardswitch) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 4.2 A max (peak current) Certification Safety USA and Canada (CSA certified), EU (LVD and EN60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICSS), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, EuP, FEMP, EPEAT Bronze		Operating tempe	rature: 5 to 40°C (41 to 104°F)	
Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep) Sound power: 6.5 B(A) (printing); 5.8 B(A) (ready); <1.9 B(A) (sleep)	ranges	Storage temperature: -25 to 55°C (-13 to 131°F)		
Sound power: 6.5 B(A) (printing); 5.8 B(A) (ready); <1.9 B(A) (sleep) Power consumption <120 watts (printing), <260 watts (maximum), <4 watts (<7 watts with embedded Digital Front End) (sleep), 0.1 watts (auto-off), 0 watts (off hardswitch) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 4.2 A max (peak current) Certification Safety USA and Canada (CSA certified), EU (LVD and EN60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, EuP, FEMP, EPEAT Bronze		Operating humidity: 20 to 80% RH		
Power consumption < 120 watts (printing), < 260 watts (maximum), < 4 watts (< 7 watts with embedded Digital Front End) (sleep), 0.1 watts (auto-off), 0 watts (off hardswitch) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 4.2 A max (peak current) Certification Safety USA and Canada (CSA certified), EU (LVD and EN60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, EuP, FEMP, EPEAT Bronze	Acoustic	Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)		
Consumption Digital Front End) (sleep), 0.1 watts (auto-off), 0 watts (off hardswitch) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 4.2 A max (peak current) Certification Safety USA and Canada (CSA certified), EU (LVD and EN60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICSS), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, EuP, FEMP, EPEAT Bronze		Sound power: 6.5 B(A) (printing); 5.8 B(A) (ready); <1.9 B(A) (sleep)		
max (peak current) Certification Safety USA and Canada (CSA certified), EU (LVD and EN60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, EuP, FEMP, EPEAT Bronze	Power consumption	< 120 watts (printing), < 260 watts (maximum), < 4 watts (< 7 watts with embedded Digital Front End) (sleep), 0.1 watts (auto-off), 0 watts (off hardswitch)		
compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, EuP, FEMP, EPEAT Bronze		Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 4.2 A max (peak current)		
rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, EuP, FEMP, EPEAT Bronze	Certification	Safety	compliant), Russia (GOST), Singapore (PSB), China (CCC),	
EPEAT Bronze		Electromagnetic	rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A	
Warranty One-year limited hardware warranty		Environmental	ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, EuP, FEMP, EPEAT Bronze	
	Warranty	One-year limited	hardware warranty	

Ordering information

Product	CR356A	HP Designjet T1500 36-in ePrinter
	CR357A	HP Designjet T1500 36-in PostScript ePrinter
Accessories	CN538A	HP Designjet 3-in Core Adapter
	COE65A	HP Designjet T9x0/Tx500 36-in Spindle
	CQ654B/ CQ654C	HP Designjet HD Scanner
Driginal HP printhead	B3P06A	HP 727 Designjet Printhead
Original HP ink cartridges	B3P17A	HP 727 40-ml Photo Black Designjet Ink Cartridge
	B3P13A	HP 727 40-ml Cyan Designjet Ink Cartridge
	B3P14A	HP 727 40-ml Magenta Designjet Ink Cartridge
	B3P15A	HP 727 40-ml Yellow Designjet Ink Cartridge
	B3P18A	HP 727 40-ml Gray Designjet Ink Cartridge
	C1Q11A	HP 727 69-ml Matte Black Designjet Ink Cartridge
	B3P23A	HP 727 130-ml Photo Black Designjet Ink Cartridge
	B3P19A	HP 727 130-ml Cyan Designjet Ink Cartridge
	B3P20A	HP 727 130-ml Magenta Designjet Ink Cartridge
	B3P21A	HP 727 130-ml Yellow Designjet Ink Cartridge
	B3P24A	HP 727 130-ml Gray Designjet Ink Cartridge
	B3P22A	HP 727 130-ml Matte Black Designjet Ink Cartridge ⁹
	C1Q12A	HP 727 300-ml Matte Black Designjet Ink Cartridge
Original HP large format printing materials	C1861A	HP Bright White Inkjet Paper (FSC® certified) ¹⁰ 43 ¹¹ 914 mm x 45.7 m (36 in x 150 ft)
	C6020B	HP Coated Paper (PEFC™ certified) ¹⁰ ⇔ ¹¹ 914 mm x 45.7 m (36 in x 150 ft)
	C6030C	HP Heavyweight Coated Paper (PEFC™ certified) ¹⁰ ∰ ¹¹ 914 mm x 30.5 m (36 in x 100 ft)
	Q1421A	HP Universal Satin Photo Paper 👶 1 914 mm x 30.5 m (36 in x 100 ft)
Service and support	U7Z08E	HP 3 year Next Business Day Onsite Support ¹²
	U7Z11E	HP 3 year Next Business Day Onsite Support with Defective Media Retention ¹³
	U7Z88E	HP 3 year 4-hour response, 9x5 Onsite Support ¹²
	U7Z91E	HP 3 year 4-hour response, 13x5 Onsite Support ¹²
	U7Z94PE	HP 1 year Post Warranty, Next Business Day Onsite Support ¹²
	U7Z95PE	HP 1 year Post Warranty Next Business Day Onsite Support with Defective Media Retention ¹³
	U7Z99PE	HP 1 year Post Warranty, 4-hour response, 13x5 Onsite Support ¹²

HP Designjet Support Services offer solutions for business critical environments — installation, extended support and maintenance, as well as variety of value added services.

For more information, please visit hp.com/go/designjet/support.

Use Original HP inks and printheads to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system to provide precise line accuracy as well as dark blacks and true neutral grays¹⁴ For more information, visit <u>hp.com/go/OriginalHPinks</u>.

For the entire HP Large Format Printing Materials portfolio, please see globalBMG.com/hp.

Mechanical printing time. Printed in Fast mode, using HP Bright White Inkjet Paper (Bond) and Original HP inks. +/-0.1% of the specified vector length or +/-0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E printing material in Best or Normal mode with HP Matte Film and HP Original HP inks. Measured on HP Matte Film.

- Based on 1.5 GB RAM.
- Includes an embedded Jetdirect print server.
- Included with PostScript printers only.
- Included with PostScript printers only. Available only in Europe, Middle East, and Africa. FSC® trademark license code FSC®-CO17543, see <u>fsc.org</u>. PEFC™ trademark license code PEFC™/29-31-198, see <u>pefc.org</u>. Not all FSC®- or PEFC™-certified products are available in all regions. Can be recycled through commonly available recycling programs.
- 12 Not available in North America, and Latin America.
- 13 Not available in Europe, Middle East, and Africa.
- Applicable to HP Designjet T-series Printers, ePrinters, and eMFPs. True neutral grays produced by printers compatible with the HP Three-black ink set. 14



For more information, please visit hp.com/go/DesignjetT1500

© Copyright 2013-2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Adobe and Adobe PostScript 3 are trademarks of Adobe Systems Incorporated. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Windows is a U.S. registered trademark of Microsoft Corporation. PANTONE is the property of Pantone, Inc. Mac and the Mac logo are trademarks of Apple Computer, Inc., registered in the U.S. and other countries

